


DATA OUTPUT

- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch
- Automatic power off, move the digital unit to turn on power
- Meet DIN862
- Battery CR2032
- Made of stainless steel

DIGITAL DOUBLE HOOK DEPTH GAGES



1144-150A



With data interface

| Code | Range | Accuracy | L | d | a | b | c | e | Data output cable (optional) |
|-------------|----------------|----------|--------|-------|--------|-------|--------|-------|------------------------------|
| 1144-150A | 0-150mm/0-6" | ±0.03mm | 233mm | 100mm | 21.5mm | 3.5mm | 14.5mm | 2.5mm | 7315-21, 7302-21 |
| 1144-200A | 0-200mm/0-8" | ±0.03mm | 283mm | 100mm | 21.5mm | 3.5mm | 14.5mm | 2.5mm | 7315-21, 7302-21 |
| 1144-300A | 0-300mm/0-12" | ±0.03mm | 383mm | 150mm | 21.5mm | 3.5mm | 14.5mm | 2.5mm | 7315-21, 7302-21 |
| 1144-500A | 0-500mm/0-20" | ±0.05mm | 585mm | 150mm | 25mm | 5mm | 15mm | 3mm | 7315-21, 7302-21 |
| 1144-5001A | 0-500mm/0-20" | ±0.05mm | 585mm | 200mm | 25mm | 5mm | 15mm | 3mm | 7315-21, 7302-21 |
| 1144-1000A | 0-1000mm/0-40" | ±0.07mm | 1188mm | 150mm | 32mm | 7mm | 18mm | 4mm | 7315-22, 7302-22 |
| 1144-10001A | 0-1000mm/0-40" | ±0.07mm | 1188mm | 200mm | 32mm | 7mm | 18mm | 4mm | 7315-22, 7302-22 |
| 1144-10002A | 0-1000mm/0-40" | ±0.07mm | 1188mm | 250mm | 32mm | 7mm | 18mm | 4mm | 7315-22, 7302-22 |

Built-in wireless

| Code | Range | Accuracy | L | d | a | b | c | e |
|--------------|---------------|----------|-------|-------|--------|-------|--------|-------|
| 1144-150AWL | 0-150mm/0-6" | ±0.03mm | 233mm | 100mm | 21.5mm | 3.5mm | 14.5mm | 2.5mm |
| 1144-200AWL | 0-200mm/0-8" | ±0.03mm | 283mm | 100mm | 21.5mm | 3.5mm | 14.5mm | 2.5mm |
| 1144-300AWL | 0-300mm/0-12" | ±0.03mm | 383mm | 150mm | 21.5mm | 3.5mm | 14.5mm | 2.5mm |
| 1144-500AWL | 0-500mm/0-20" | ±0.05mm | 585mm | 150mm | 25mm | 5mm | 15mm | 3mm |
| 1144-5001AWL | 0-500mm/0-20" | ±0.05mm | 585mm | 200mm | 25mm | 5mm | 15mm | 3mm |

