

STROJNÍ ZÁVITNÍK S PŘÍMOU DRÁŽKOU

Machine tap with straight flutes

 Maschinengewindebohrer mit geraden Nuten

 Машинный метчик с прямой канавкой


 Maschi a macchina con taglienti dritti

 Düz Kanal Makina Kılavuzu

TYPE
N

3004

3014



TiN

UNC

60°
F

HSSE

≈DIN
376

2B

C
2-3

$\sqrt{1,5\phi}$

$\sqrt{1,5\phi}$

d_1	tpi	l_1	l_2	d_2	a	z	ϕ		
UNC 7/16	14	100	20	8	6,2	3	9,4	•	•
UNC 1/2	13	110	23	9	7	3	10,75	•	•
UNC 9/16	12	110	25	11	9	3	12,25	•	•
UNC 5/8	11	110	25	12	9	3	13,5	•	•
UNC 3/4	10	125	30	14	11	3	16,5	•	•
UNC 7/8	9	140	30	18	14,5	3	19,5	•	•
UNC 1	8	160	36	18	14,5	3	22,25	•	•
UNC 1 1/8	7	180	40	22	18	4	25	•	•

Řezné podmínky / Cutting conditions / V_c

P1.1	Konstrukční oceli / Structural steels <500N/mm ²	4-6	5-8
P2.1	Automatové oceli / Free-cutting steels <800N/mm ²	8-10	10-14
K6.1	Šedá litina / Grey cast iron	7-10	8-12
N8.2	Legovaný hliník / Aluminium alloys Si>10%	12-15	14-20
N10.1	Slitiny mědi s krátkou třískou / Short chipping copper alloys	10-15	15-25

narex[®]
žďanice