



# STROJNÍ ZÁVITNÍK SE ŠROUBOVITOU DRÁŽKOU 40°

Machine tap with right-hand spiral flutes 40°



Maschinengewindebohrer mit 40° RSP, rechtsschneidend



Машинный метчик со спиральной канавкой 40°



Maschi a macchina con taglienti elicoidali destri 40°




40° Helis Makina Kılavuzu

TYPE  
VA

4320

4320IKZ



**M**

d <sub>1</sub>	P	l <sub>1</sub>	l <sub>2</sub>	d <sub>2</sub>	a	z	∅	HL	HL
M 12	1,75	110	18	9	7	3	10,2	•	•
M 14	2	110	20	11	9	3	12	•	
M 16	2	110	20	12	9	4	14	•	
M 18	2,5	125	25	14	11	4	15,5	•	
M 20	2,5	140	25	16	12	4	17,5	•	



DIN  
13



DIN  
376



ISO 2  
6H



C  
2-3



40°



N9.1

## Řezné podmínky / Cutting conditions / V<sub>c</sub>

P3.1	Cement. a nitr. / Case hardened and nitriding steels	6-8	6-8
P3.2	Zušlechtěné oceli / Heat-treated steels <1200N/mm <sup>2</sup>	4-6	4-6
P3.3	Nástrojové oceli / Tool steels	6-8	6-8
M5.1	Nerezavějící oceli / Stainless steels 450-800N/mm <sup>2</sup>	8-14	8-14
M5.2	Nerezavějící oceli / Stainless steels 600-1000N/mm <sup>2</sup>	6-10	6-10
N9.1	Měď čistá / Pure copper	10-15	10-15
N10.2	Slitiny mědi s dlouhou tráskou / Long chipping copper alloys	12-20	12-20

**narex®**  
zdánice