

# Produktinformation

## Digital indicator MarCator1086 Ri



### Application:

Comprehensive measuring function for static measurements such as lengths, distances and length differences

### Function:

ON/OFF, RESET (set display to zero), mm/inch, Reversal of counting direction, PRESET (for entering a numerical value), TOL (enter tolerance limit values), <0> (tolerance GO / NO GO display mode), ABS (display can be set to zero without losing reference to preset), DATA (data transmission via connection cable), Factor (adjustable), LOCK (individual key lock)



### Product features:

- Integrated wireless transmitter
- High contrast LCD
- Operating and display unit (bezel) can be rotated through 280°
- Mounting shank and measuring spindle are both made of hardened stainless steel
- Immediate measurements due to the Reference System

Artikel-Nr.: 4337626

### Technische Daten


<b>Measuring span</b>	50 mm
<b>Measuring range in inch</b>	2 in
<b>Resolution</b>	0,0005 mm, 0,001 mm, 0,002 mm, 0,005 mm, 0,01 mm
<b>Resolution inches</b>	.00002", .00005", .0001", .0002", .0005"
<b>Error limit</b>	0,007 mm
<b>Error limit over 25 graduations</b>	0,002 mm
<b>Repeatability mm</b>	0,001 mm
<b>Measuring force</b>	1.25 - 2.7
<b>Height of digits</b>	11 mm

### Package contains:

- instruction manual
- battery

### Abmessungen

<b>Mounting shaft</b>	8 mm
<b>a</b>	267,3 mm
<b>b</b>	40 mm
<b>c</b>	52 mm



### Zubehör

Bezeichnung	Typ	Artikel-Nr.
Receiver for instruments with integrated wireless	i-Stick	4102220
Data connection cable USB	16 EXu	4102357
Digimatic data cable	16 EWd	4102915
Data connection cable RS232C	16 EXr	4102410
Lug back	1086 b	4337421
Pneumatic Lifter	1082 p	4336230
Adapter bush	940	4310103