

# Produktinformation

## Digital indicator MarCator1086 R



### Application:

Comprehensive measuring function for static measurements such as lengths, distances and length differences

### Function:

ON/OFF, RESET (set display to zero), mm/inch, Reversal of counting direction, PRESET (for entering a numerical value), TOL (enter tolerance limit values), <0> (tolerance GO / NO GO display mode), ABS (display can be set to zero without losing reference to preset), DATA (data transmission via connection cable), Factor (adjustable), LOCK (individual key lock)



### Product features:

- High contrast LCD
- Operating and display unit (bezel) can be rotated through 280°
- Lifter protection cap on the measuring spindle
- Mounting shank and measuring spindle are both made of hardened stainless steel
- Immediate measurements due to the Reference System

Artikel-Nr.: 4337620

### Technische Daten

Measuring span	12,5 mm
Measuring range in inch	0,5 in
Resolution	0,0005 mm, 0,001 mm, 0,002 mm, 0,005 mm, 0,01 mm
Resolution inches	.00002", .00005", .0001", .0002", .0005"
Error limit	0,004 mm
Error limit over 25 graduations	0,002 mm
Repeatability mm	0,001 mm
Measuring force	0.65 - 0.9
Height of digits	11 mm

### Energy supply:


Battery life approx. 3 years

### Package contains:

- instruction manual
- battery

### Abmessungen

Mounting shaft	8 mm
a	126,3 mm
b	23 mm
c	13,5 mm



### Zubehör

Bezeichnung	Typ	Artikel-Nr.
Data connection cable USB	16 EXu	4102357
Digimatic data cable	16 EWd	4102915
Data connection cable RS232C	16 EXr	4102410
Lug back	1086 b	4337421
Cable release	1085 a	4336311
Pneumatic Lifter	1082 p	4336237
Adapter bush	940	4310103