

Produktinformation

Digital indicator MarCator1086 R



Application:

Comprehensive measuring function for static measurements such as lengths, distances and length differences

Function:

ON/OFF, RESET (set display to zero), mm/inch, Reversal of counting direction, PRESET (for entering a numerical value), TOL (enter tolerance limit values), <0> (tolerance GO / NO GO display mode), ABS (display can be set to zero without losing reference to preset), DATA (data transmission via connection cable), Factor (adjustable), LOCK (individual key lock)



Product features:

- High contrast LCD
- Operating and display unit (bezel) can be rotated through 280°
- Lifter protection cap on the measuring spindle
- Mounting shank and measuring spindle are both made of hardened stainless steel
- Immediate measurements due to the Reference System

Artikel-Nr.: 4337622

Technische Daten

| | |
|---------------------------------|--|
| Measuring span | 50 mm |
| Measuring range in inch | 2 in |
| Resolution | 0,0005 mm, 0,001 mm, 0,002 mm, 0,005 mm, 0,01 mm |
| Resolution inches | .00002", .00005", .0001", .0002", .0005" |
| Error limit | 0,007 mm |
| Error limit over 25 graduations | 0,002 mm |
| Repeatability mm | 0,001 mm |
| Measuring force | 1.25 - 2.7 |
| Height of digits | 3,5 mm |

Energy supply:


Battery life approx. 3 years

Package contains:

- instruction manual
- battery

Abmessungen

| | |
|----------------|----------|
| Mounting shaft | 8 mm |
| a | 267,3 mm |
| b | 40 mm |
| c | 52 mm |



Zubehör

| Bezeichnung | Typ | Artikel-Nr. |
|------------------------------|--------|-------------|
| Data connection cable USB | 16 EXu | 4102357 |
| Digimatic data cable | 16 EWd | 4102915 |
| Data connection cable RS232C | 16 EXr | 4102410 |
| Lug back | 1086 b | 4337421 |
| Pneumatic Lifter | 1082 p | 4336230 |
| Adapter bush | 940 | 4310103 |