

Produktinformation

Digital indicator MarCator1086 R



Application:

Comprehensive measuring function for static measurements such as lengths, distances and length differences

Function:

ON/OFF, RESET (set display to zero), mm/inch, Reversal of counting direction, PRESET (for entering a numerical value), TOL (enter tolerance limit values), <0> (tolerance GO / NO GO display mode), ABS (display can be set to zero without losing reference to preset), DATA (data transmission via connection cable), Factor (adjustable), LOCK (individual key lock)



Product features:

- High contrast LCD
- Operating and display unit (bezel) can be rotated through 280°
- Lifter protection cap on the measuring spindle
- Mounting shank and measuring spindle are both made of hardened stainless steel
- Immediate measurements due to the Reference System

Artikel-Nr.: 4337623

Technische Daten

Measuring span	100 mm
Measuring range in inch	4 in
Resolution	0,0005 mm, 0,001 mm, 0,002 mm, 0,005 mm, 0,01 mm
Resolution inches	.00002", .00005", .0001", .0002", .0005"
Error limit	0,008 mm
Error limit over 25 graduations	0,002 mm
Repeatability mm	0,001 mm
Measuring force	1.8 - 3.5
Height of digits	11 mm

Energy supply:


Battery life approx. 3 years

Package contains:

- instruction manual
- battery

Abmessungen

Mounting shaft	8 mm
a	420,3 mm
b	91 mm
c	103 mm



Zubehör

Bezeichnung	Typ	Artikel-Nr.
Data connection cable USB	16 EXu	4102357
Digimatic data cable	16 EWd	4102915
Data connection cable RS232C	16 EXr	4102410
Lug back	1086 b	4337421
Pneumatic Lifter	1082 p	4336230
Adapter bush	940	4310103