


RCGT

	d	d ₁	s
0803	8,000	3,40	3,18
1003	10,000	4,40	3,18




i	ISO	Material	P	M	K	N	S	H	?	Lubrication	r _ε	f _{min}	f _{max}	a _{p min}	a _{p max}
	RCGT 0803MOF-AL	T0315				■			●	+	-	0,20	1,50	0,8	3,0
		HF7				■			●	+	-	0,20	1,50	0,8	3,0
	RCGT 1003MOF-AL	T0315				■			●	+	-	0,20	2,00	1,0	4,0
		HF7				■			●	+	-	0,20	2,00	1,0	4,0



RCMH

	d	d ₁	s
3209	32,000	10,50	9,525



i	ISO	Material	P	M	K	N	S	H	?	Lubrication	r _ε	f _{min}	f _{max}	a _{p min}	a _{p max}
	RCMH 3209MO-RM2	T9310	■		▣				●	++	-	0,80	1,30	2,0	8,0
		T9315	■		▣				●	++	-	0,80	1,30	2,0	8,0
		T9325	■	□	▣				●	✘	++	-	0,80	1,30	2,0
	RCMH 3209MO-RR2	T9310	■		▣				●	++	-	0,80	1,50	2,5	8,0
		T9315	■		▣				●	++	-	0,80	1,50	2,5	8,0
		T9325	■	□	▣				●	✘	++	-	0,80	1,50	2,5