


RNMG


	d	d ₁	s
1204	12,700	5,16	4,76
1506	15,875	6,35	6,35
1906	19,050	7,94	6,35
2509	25,400	9,12	9,525



i	ISO	Material	P	M	K	N	S	H	?	Drop	r _ε	f _{min}	f _{max}	a _{p min}	a _{p max}
 	RNMG 120400E-08	T5305	☐		■			■	●	+	-	0,30	0,80	1,0	4,8
		T9315	■		■			■	●	++	-	0,30	0,80	1,0	4,8
		T9325	■		■				●	+	-	0,30	0,80	1,0	4,8
 	RNMG 150600E-08	T5305	☐		■			■	●	+	-	0,30	0,80	1,0	6,0
		T9315	■		■			■	✘	++	-	0,30	0,80	1,0	6,0
		T9325	■		■				✘	+	-	0,30	0,80	1,0	6,0
 	RNMG 190600E-08	T9315	■		■			■	●	++	-	0,30	0,80	1,0	6,0
		T9325	■		■				●	+	-	0,30	0,80	1,0	6,0
 	RNMG 250900E-081	T9315	■		■				✘	++	-	0,80	1,20	3,0	7,0
		T9325	■	■	■				✘	++	-	0,80	1,20	3,0	7,0

SCGT

	d	d ₁	l	s
09T3	9,525	4,40	9,525	3,97
09T3-SF3	9,525	4,40	9,525	4,22
1204	12,700	5,50	12,700	4,76



i	ISO	Material	P	M	K	N	S	H	?	Drop	r _ε	f _{min}	f _{max}	a _{p min}	a _{p max}
 	SCGT 120408F-AL	T0315				■			●	+	0,8	0,15	0,60	0,8	7,0
		HF7					■			●	+	0,8	0,15	0,60	0,8